



| 型式 TYPE | 伝熱面積 HEAT TRANSFER AREA | A | B | C | Dφ | E | F | H | N-Hφ | 重量 WEIGHT |
|------------|----------------------------|------|-----|-----|-------|------|-----|-----|-------|--------------|
| HCR-KT- 40 | 0.25 m ² | 1000 | 900 | 50 | 48.6 | 40A | 20A | 49 | 4-19 | 5.5 kg |
| HCR-KT- 50 | 0.47 | 1000 | 890 | 55 | 60.5 | 50A | 25A | 59 | 4-19 | 7.0 |
| HCR-KT- 65 | 0.9 | 1000 | 880 | 60 | 76.3 | 65A | 32A | 70 | 4-19 | 11.0 |
| HCR-KT- 80 | 1.38 | 1000 | 870 | 65 | 89.1 | 80A | 40A | 78 | 8-19 | 13.0 |
| HCR-KT-100 | 2.2 | 1000 | 860 | 70 | 114.3 | 100A | 50A | 95 | 8-19 | 17.0 |
| HCR-KT-125 | 3.5 | 1000 | 860 | 70 | 139.8 | 125A | 50A | 110 | 8-23 | 24.0 |
| HCR-KT-150 | 5.0 | 1000 | 830 | 85 | 165.2 | 150A | 65A | 127 | 8-23 | 32.0 |
| HCR-KT-200 | 8.8 | 1000 | 800 | 100 | 216.3 | 200A | 80A | 150 | 12-23 | 67.0 |

| | | | | |
|------------|--------------------------|-----------------|-----------|---------------|
| 5 | ノズルソケット NOZZLE SOCKET | SUS304 | 2 | |
| 4 | バッフル BUFFLE | SUS304 | 5 | |
| 3 | チューブ TUBE | TITAN | | |
| 2 | シェル SHELL | SUS304 | 1 | |
| 1 | ノズルフランジ NOZZLE FLANGE | SUS329J4L | 2 | |
| 品番 ITEM | 部品名称 NAME | 材質 MATERIALS | 数量 QTY | 備考 REMARKS |

HCR-KT

図面番号
DWG.No.
REFERENCE DRAWING

株式会社
ZENSHIN CO.,LTD
JAPAN